

A6510

A7510

A8610

GENERAL

Front Interface	HDMI x1, USB C x1, USB A 3.0 x2, USB B 3.0 x1, MIC In x1		
Rear Interface	USB A x3, USB C x1, USB B x3, HDMI In x2, DisplayPort x1, OPS Slot x1, RS232 x1, Audio Out x1, Line out or Headphone x1, SPDIF x1, HDMI Out x1, LAN 1000Base-T x2		
Pre-installed app	Whiteboard, Picture-In-Picture, Eshare, Browser, Settings, Google Play Store, Google Calender, Files by Google, Search, Chrome, Gmail, Maps, YouTube, Drive, YT Music, Google TV, Meet, Photos		
Dimensions: W x D x H (mm)	1,513 x 93 x 953	1,735 x 92 x 1,077	1,981 x 92 x 1,217
Package size: W x D x H (mm)	1,630 x 185 x 1,057	1,859 x 227 x 1,190	2,119 x 225 x 1,320
Weight (kg)	40	52	65
Housing material (face frame/back shell)	Aluminium/metal plate		
Housing colour (face frame/back shell)	Black/black		
VESA	4-M8 screw hole 600 x 400 mm	4-M8 screw hole 800 x 400 mm	4-M8 screw hole 800 x 400 mm

DISPLAY PANEL

Panel size: diagonal	65" wide	75" wide	86" wide
Effective area: W x H (mm)	1,428 x 803	1,650 x 928	1,895 x 1,065
Resolution: maximum (Full HD)	3,840 x 2,160		
Colours: maximum	1,070,000,000		
Brightness: maximum (cd/m ²)	400		
Contrast ratio	5,000 : 1	5,500 : 1	4,000 : 1
Pixel pitch (mm)	0.124 x 0.372	0.14325 x 0.42975	0.4935 x 0.4935
Response: grey to grey (ms)	6.5	6.5	8
Refreshing frequency	60 Hz		
Viewing angle: H/V (°)	178/178		
LED lifetime	50,000 hours		

TOUCH SYSTEM

Touch technology	Infrared Touch Frame/Zero Bonding		
Accuracy (mm in touchable area)	1		
Multi touch	Win11/10/8/7/XP, Android		
Single touch	Linux, Mac OS X, Chrome		
Protection glass thickness: including AR coating (mm)	3.2		
Maximum touch points	40		
Coating	Anti-glare, Anti-fingerprint		
Hardness	8 H		

ECOLOGY

Power consumption: standard mode (W)	< 200		
Power consumption: eco mode (W)	< 133	< 150	< 168
Power consumption: standby mode (W)	< 0.5		
Power consumption: with OPS (W)	< 380	< 420	< 520
Operating temperature (°C)	0 - 40		
Operating humidity (%)	20 - 80		
Altitude limitation: sea level (m)	Lower than 5,000		
Maximum daily operation hours (exclude stand-by time)	Do not use the machine continuously/intermittently for more than 18 hours per day. Failure to do so could result in malfunction.		
Storage temperature	-10°C ~ +50°C		
Storage humidity	15% ~ 80% RH Non-Condensing		

CONTROLLER/ELECTRICAL

OS	Android 13.0 EDLA		
Audio output power	15 W x2		
RAM	8 GB		
ROM Storage	128 GB		
WIFI	Wif5 Module, Wif6 Module		
Bluetooth	BT 5.2		

A6510

A7510

A8610

ACCESSORIES

Power cable
Touch pen x2
Read this first sheet
Quick guide sheet
Batteries AAAx2
Remote control
USB type C cable (2m)
HDMI 2.0 cable (3m)
USB A-B 3.0 cable (3m)
Plastic clamp(3pcs+3pcs)

For availability of models, options and software, please consult your local supplier.

Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands



+31 (0)20 5774111



[ricoh-europe.com](https://www.ricoh-europe.com)