



## Delock HDMI to DisplayPort cable 4K 30 Hz 2 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with DisplayPort connector to a HDMI interface.



2 m

## Specification

## Connectors:

- 1 x HDMI-A male
- 1 x USB Type-A male (power supply) >
- 1 x DisplayPort male
- Signal direction: HDMI input > DisplayPort output
- Chipset: STDP2600
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- Contacts gold-plated
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- 2 x ferrite core
- Colour: black
- Length incl. connectors: ca. 2 m

System requirements

• A free HDMI female

Package content

HDMI to DisplayPort cable

Images



ltem no. 85964

EAN: 4043619859641

Country of origin: China

Package: Zip poly bag





| General                    |                      |
|----------------------------|----------------------|
| Specification:             | DisplayPort 1.2      |
|                            | High Speed HDMI      |
| Interface                  |                      |
| Connector 1:               | 1 x HDMI-A male      |
|                            | 1 x USB Type-A male  |
| Connector 2:               | 1 x DisplayPort male |
| Technical characteristics  |                      |
| Chipset:                   | STDP2600             |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz  |
| Physical characteristics   |                      |
| Ferrite core:              | 2 x                  |
| Pin finishing:             | gold-plated          |
| Conductor material:        | copper               |
| Conductor gauge:           | 28 AWG               |
| Shielding:                 | triple               |
| Diameter:                  | 7.2 mm               |
| Length:                    | 2 m                  |
| Colour:                    | black                |