


NEC MultiSync® EA272F
LCD 27" Enterprise Display

Datasheet



Powering workspace communications

Powering your PC/notebook and all your devices through a single cable, the MultiSync® EA272F is your workspace hub; no docking station required, the 65W USB-C connection means an efficient, clutter-free workstation from which to manage your communications. Easily increase your display area using DisplayPort-out to daisy-chain multiple displays, no additional cabling required.

User comfort is fundamental with full height adjustment, tilt, pivot and swivel supporting customised personal setup, whilst built-in low blue light technologies guard against eye fatigue without compromising true-to-life colour performance. Available in black or white, the 27" EA272F complements office interior design and ergonomics.

The connectivity advantage continues beyond USB Type-C with DisplayPort, HDMI, VGA and USB A for fully future-proof flexibility supporting new open office standards in hot desking and 'bring your own device.'

Benefits

In-demand display size - the popular 27.0" display with Full HD resolution is the perfect size for busy office workspaces.

Clutter-free workspace - Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable

Future-proof flexibility - wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.

Easy multi-screen set-up - Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed

Maximum attention to health and well-being - the outstanding ergonomic height adjustment from 0 to 150 mm; eye pleasing built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to tailor the perfect individual setup to boost productivity.

Product Information

Product Name	NEC MultiSync® EA272F
Product Group	LCD 27" Enterprise Display
Order Code	60005247 (WH), 60005033 (BK)

Display

Panel Technology	AH-IPS LCD with LED Backlight
Screen Size [inch/cm]	27 / 69
Screen Aspect Ratio	16:9
Colour Gamuts	102 % sRGB; 75.5% AdobeRGB, 72% NTSC
Pixel Pitch [mm]	0.311
Brightness (typ.) [cd/m ²]	250
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.777

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

Resolution

Optimum Resolution	1920 x 1080 at 60 Hz			
Supported	1920 x 1080; 1680 x 1050; 1440 x 900;	1280 x 1024; 1280 x 960; 1280 x 720;	1024 x 768; 800 x 600; 720 x 400 (70 Hz);	640 x 480

Connectivity

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up)
Analog	1 x VGA

Electrical

Power Consumption on Mode [W]	15 (Eco Mode 2); 21 (typ.)
Power Savings Mode [W]	3
Power Supply	0.85 A/0.45 A; 100-240 V; integrated power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

Ergonomics

Height adjustable stand [mm]	150 (Landscape mode)
Screen Tilt [°]	-5 to 35
Screen Swivel [°]	-170 to 170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

Mechanical

Bezel Width [mm]	0.8 (left and right); 0.8 (top); 15.8 (bottom)
Dimensions (W x H x D) [mm]	359.8 x 628.4 - 651.6 x 250 (Portrait mode); 610.2 x 377.3 - 527.3 x 250 (Landscape mode)
Weight [kg]	With stand: 9.2
VESA Mounting [mm]	100 x 100

Additional Features

Special Characteristics	Ambient light sensor for optimized brightness levels; Auto Contrast; Carbon Footprint Meter; Carbon Savings Meter; ControlSync®; Customize Setting; DICOM simulation; EcoModes; ErgoDesign®: Height adjustable stand (150 mm) with 90° Pivot features; Human Sensor; LED Backlight Technology; Quick release Stand and Handle; USB ver. 3.1 (3 down / 1 up); Versatile and easy installation (VESA standard) with NaViSet and NaViKey; Windows 10 compatible
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	DDC2B/2Bi; EDID Standard; VESA DDC/CI
Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Factory Preset; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Set-up Manual; Setup Guide; USB Cable; USB-C Cable
Safety and Ergonomics	CE; EAC; EnergyStar 8.0; ErP; FCC Class B; Flicker-free; ISO 9241-307 (pixel failure class 2); ISO 9241-307 (pixel failure class I); Low Blue Light; PSB; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 4th to 5th year warranty extension

Green Features

Energy Efficiency	Ambient light sensor; Auto brightness; Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy consumption: 15 kWh/1000 h; Energy efficiency class: D; Human sensor; LED backlight technology
Ecological Materials	Efficient mechanical design for minimised packaging; Minimal use of harmful material
Ecological Standards	ErP compliant; TCO 7.0; WEEE



CE



ErP



FCC Class B



RoHS



TCO 8.0



TÜV
Ergonomics



TÜV GS

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 20.04.2021